# BAY AREA SELF STORAGE

10655 MARY AVE. CUPERTINO, CA 95014



DIREC	TORY				
OWNER	CIVIL ENGINEER	В	ASIS (	OF DESIGN	
BASS CUPERTINO, LLC	SANDIS			REQUIRED	PROVIDED
10121 MILLER AVE. #200 CUPERTINO, CA 95014	636 9th STREET OAKLAND, CA 94607	ZONE		P (BQ, MINI-STOR)	
PH: (408) 255 4100 FX: (408) 966 8425 CONTACT: CURTIS LEIGH	PH: (510) 873 8866 CONTACT: RONALD SANZO EMAIL: rzonzo@sandis.net	STRUCTURE HEIGHT		30 FT. ABOVE NATURAL GRADE	30 FT. ABOVE NATURAL GRADE
PH: (408) 350 5354 EMAIL: curtis@hunterproperties.com		FLOOR AREA RATIO		1.0	0.95 (166,845 S.F.)
ARCHITECT BRUCE JORDAN ARCHITECT	LANDSCAPE PLEINAIRE DESIGN GROUP 3203 LIGHTNING ST. SUITE 201	LOT COVERAGE (EXCLUDES LO AREAS, RECESSED ENTRANCES COURTYARD)		40% (70,065 S.F.)	40% (70,278 S.F.)
131 CALLE IGLESIA, SUITE 100 SAN CLEMENTE, CA 92673	SANTA MARIA, CA 93455-1805	SETBACKS:			
PH: (949) 388-8090 FX: (949) 388-8290	PH: (805) 349 9695 FX: (805) 928 4689		FRONT	40 FT.	40 FT.
CONTACT: BRUCE JORDAN	CONTACT: KEVIN J. SMALL EMAIL: kjsmall@pleinairedg.com		SIDE	5 FT.	5 SF.
CAROLINA PAZ E-MAIL: bjordan@jordanarchitects.com cpaz@jordanarchitects.com	LIVIAIL. NSITIAII@pielitaileug.com		REAR	10 FT.	0 FT. (EXISTING BLDG. TO REMAIN
CODE		INTERIOR LANDSCAPING		2,500 SF. MIN.	20,542 SF.
THIS PROJECT SHALL COMPLY W THE CALIFORNIA FIRE (CFC) & BUILD EDITION, AS ADOPTED BY THE CITY ( CODE (CMC) AND CALIFORNIA CODE	ING (CBC) CODE, 2016 OF CUPERTINO MUNICIPAL	PARKING SPACES		EXCEPTION TO: CMC 19.124.040(A)	40 SPACES
		PARKING SIZE		8.5' X 18' PER CMC 19.124.040(J)	STANDARD: 9' X 18'
CONSTRUCTION NOTES:		BICYCLE PARKING - CLASS 1		EXCEPTION REQUEST 1 BIKE / 12,000 SF CMC 19.124.040 (A) 167,044 / 12,000 = 14	2 SPACES
1. THIS PROJECT WILL BE LEED OF WITH THE CITY OF CUPERTINO OF CUPERTINO OF PROPERTY.  3. A COMPLETED CONSTRUCTION RECYCLING PLANS MUST BE SET THE DEMOLITION AND OF REIN	RDINANCE.  T BE PERMITTED ON THE  N AND DEMOLITION (C&D)  UBMITTED IN ADVANCE OF	BIKE & VEHICLE PARKING EXCEPTION  166,845 / 450 = 371 TOTAL VEHICLE PARKING ALLOWED PARKING SPACES = 41  41 SPACES / 371 SPACES = 9.0% OF TOTAL  166,845 / 12,000 = 14 TOTAL BIKE PARKING S  14 X 9.9% = 2 TOTAL BIKE PARKING SPACES	SPACES SPACES	ET A.10)	

BUILDING CONSTRUCTION TYPE: IIB


OCCUPANCY CLASSIFICATION: S-1.

ACCORDANCE WITH NFPA 13.

OT AREA	175,735	SQ. FT.
	4.03	ACRES
EXISTING BLDG. UNIT COUNT	52	
NEW BLDGS. UNIT COUNT	1,074	
TOTAL STORAGE UNIT COUNT	1,126	
PARKING PROVIDED		
STANDARDS OR LARGER	34	
VAN ACCESSIBLE	2	
CLEAN AIR/VANPOOL/EVC	3	
MANAGER SPACE	1	
RESIDENTIAL GARAGE	1	
TOTAL	41	

PROJECT DATA

BUILDING AR	REA TABUL	ATION (Squa	re Feet)
BUILDING	SELF STORAGE	OFFICE & RESIDENCE	GROSS AREA
BUILDING A			119,747
1st LEVEL	38,809	0	
2nd LEVEL	38,969	0	
3rd LEVEL	41,969	0	
BUILDING B		0	28,568
1 st LEVEL	14,234	0	
2nd LEVEL	14,334	0	
BUILDING C			5,012
OFFICE	0	1,271	
MGR. RESIDENCE	0	1,271	
GARAGE	0	279	
COURTYARD	0	237	
STORAGE	1,954	0	
BUILDING D (Existing to Remain)	13,518		13,518
TOTAL	163,787	3,058	166,845



**VICINITY MAP** 

# A.1.1 COA - PUBLIC WORKS A.1.2 COA - ENVIRONMENTAL PROG. DIV A.16 DETAILS



#### GENERAL NOTES:

1. ALL UTILITY DISTRIBUTION INSTALLED IN AND FOR THE PURPOSE OF SUPPLYING SERVICE TO ANY DEVELOPMENT AREA WITHIN THE CITY, SHALL BE PLACED UNDERGROUND; CMC SECTION 14.24.030.

. DEFERRED PERMIT: SIGNAGE

SPRINKLER SYSTEM.

- ALARM SYSTEM.

C0.1 TOPO + SURVEY BOUNDARY SURVEY (FOR REFERENCE ONLY) C1.0 PRELIMINARY SITE + EASEMENT PLAN

SHEET INDEX

**ARCHITECTURAL** 

C2.0 PRELIMINARY GRADING AND UTILITY PLAN

C2.1 PRELIMINARY SITE AND GRADING ENLARGEMENT PLAN C3.0 PRELIMINARY STORMWATER MANAGEMENT PLAN

#### LANDSCAPE

CLP-01 CONCEPTUAL LANDSCAPE PLAN A, B, & C

CLP-03 PLANT IMAGERY & AREA MAP

CLP-02 TREE REPLACEMENT PLAN

#### PLUMBING FIXTURE CALCULATION

#### OCCUPANT LOAD PER CPC 422.1, TABLE A GROUP S: 163,787 / 5000 = 33 OCCUPANTS (17 MEN, 17 WOMEN)

GROUP B: 1,271 S.F. / 200 = 7 OCCUPANTS (4 MEN, 4 WOMEN)

#### FIXTURE CALCULATION PER TABLE 422.1: CALCULATION FOR MEN

GROUP S: 17 OCCUPANTS AT RATIO OF 1:100

GROUP B: 4 OCCUPANTS AT RATIO OF 1:50 GROUP B: 4 OCCUPANTS AT RATIO OF 1:100

FRACTIONAL NUMBERS RESULTING FROM FIXTURE RATIO: GROUP S: 17 / 100 = 0.17 GROUP B: 4 / 50 = 0.08 (WC), AND 4 / 100 = 0.04 (UR) REQUIRED FIXTURE CALCULATION: 0.17 + 0.08 + 0.04 = 0.29 OR 1 WCFIXTURES PROVIDED:

LAVATORIES (LAV)

FIXTURES PROVIDED:

1. PER TABLE 2902.1, (1) SERVICE SINK IS REQUIRED.

2. TOTAL FIXTURES PROVIDED: (1) WATER CLOSET AND (1)

LAVATORY, (1) HIGH-LOW DRINKING FOUNTAIN, AND (1)

SERVICE SINK. PER CBC SECTION 2902.2 EXCEPTION 2,

SEPARATE FACILITIES FOR EACH SEX ARE NOT REQUIRED

FOR SPACES WITH A TOTAL OCCUPANT LOAD OF 15 OR

3. PER CBC SECTION 2902.3 EXCEPTION 2, PUBLIC TOILET

FACILITIES SHALL NOT BE REQUIRED FOR SPACES INTENDED

FOR QUICK TRANSACTIONS THAT ARE LESS OR EQUAL TO

300 S.F. SINCE EACH STORAGE UNIT IS BEING USED ONLY

FOR PICK-UP AND DROP-OFF AND DOES NOT EXCEED 300

S.F., THE OCCUPANTS ASSOCIATED WITH THE STORAGE

UNITS HAVE BEEN REMOVED FROM THE PLUMBING FIXTURE

4. UNISEX TOILET AND DRINKING FOUNTAINS AT THE OFFICE

AREA TO BE AVAILABLE TO ALL CUSTOMERS DURING

BUSINESS HOURS WITH NO SPECIAL ACCESS CODE

GROUP S: 17 OCCUPANTS AT RATIO OF 1:200 GROUP B: 4 OCCUPANTS AT RATIO OF 1:75 FRACTIONAL NUMBERS RESULTING FROM FIXTURE RATIO:

GROUP S: 17 / 200 = 0.09 GROUP B: 4 / 75 = 0.05 REQUIRED FIXTURE CALCULATION: 0.09 + 0.05 = 0.14 OR 1 LAV

#### **CALCULATION FOR WOMEN**

WATER CLOSETS (WC) GROUP S: 17 OCCUPANTS AT RATIO OF 1:100 GROUP B: 4 OCCUPANTS AT RATIO OF 1:15 FRACTIONAL NUMBERS RESULTING FROM FIXTURE RATIO: GROUP S: 17 / 100 = 0.17 GROUP B: 4 / 15 = 0.27

0.17 + 0.27 = 0.44 OR 1 WATER REQUIRED FIXTURE CALCULATION: CLOSET FIXTURES PROVIDED: 1 WATER CLOSET

LAVATORIES (LAV) GROUP S: 17 OCCUPANTS AT RATIO OF 1:200 GROUP B: 4 OCCUPANTS AT RATIO OF 1:50 FRACTIONAL NUMBERS RESULTING FROM FIXTURE RATIO: GROUP S: 17 / 200 = 0.09

GROUP B: 4/50 = 0.08REQUIRED FIXTURE CALCULATION: 0.09 + 0.08 = 0.17 OR 1 LAV FIXTURES PROVIDED:

# BAY AREA SELF STORAGE

BUILDINGS ARE EQUIPPED WITH AUTOMATIC FIRE SPRINKLER SYSTEM IN

TITLE SHEET

THIS DRAWING AND ITS CONTENTS ARE INSTRUMENTS OF ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN YEAR OF FIRST PUBLICATION 2018 JORDAN ARCHITECTS, INC.

N.T.S. 01/25/2021

I CALLE IGLESIA, SUITE 1 SAN CLEMENTE, CA 92672-7541

ARCHITECTS, INC



THE DEMOLITION AND/OR BUILDING PERMIT ISSUANCE.

UPON COMPLETION OF THE DEMOLITION AND/OR

FINAL APPROVAL, A C&D RECYCLING REPORT

DIVERTED FROM LANDFILL AND RECYCLED OR

ANY CONTAMINATED SOIL MUST BE CONTAINED.

BUILDING PROJECT AND PRIOR TO RECEIVING THE

INCLUDING ALL RECYCLING AND DISPOSAL WEIGHT

TICKETS MUST BE SUBMITTED, DEMONSTRATING A

MINIMUM OF 65% OF THE C&D MATERIALS HAVE BEEN

RECOVERED. FURTHERMORE, PURSUANT TO CALGREEN

SECTION 5.408.3, 100% OF EXCAVATED SOIL AND LAND

CLEARING DEBRIS SHALL BE REUSED OR RECYCLED.

TRANSPORTED, AND DISPOSED ACCORDING TO ALL

APPLICABLE LOCAL, STATE AND FEDERAL LAWS. IF

APPROVED BY THE ENVIRONMENTAL PROGRAMS

MULTIPLE DEMOLITION OR BUILDING PERMITS WILL BE

ISSUED IN PHASES FOR THIS PROJECT, C&D PLANS AND

REPORTS MUST BE SUBMITTED FOR EACH PERMIT. ALL

DIVISION PRIOR TO RELEASE OF HOLDS ON THE FINAL

C&D DEBRIS BOX SERVICE MAY ONLY BE OBTAINED

FROM RECOLOGY, THE CITY'S FRANCHISED WASTE

INSPECTION AND/OR OCCUPANCY. PLEASE NOTE THAT

C&D PLANS AND REPORTS MUST BE SUBMITTED TO AND

UTILIZE BEST MANAGEMENT PRACTICES (BMPS), AS REQUIRED BY THE STATE WATER RESOURCES CONTROL BOARD, FOR CONSTRUCTION ACTIVITY, WHICH DISTURBS SOIL. BMP PLANS SHALL BE INCLUDED IN GRADING AND STREET

#### NPDES CONSTRUCTION GENERAL PERMIT

WHEN AND WHERE IT IS REQUIRED BY THE STATE WATER RESOURCES CONTROL BOARD (SWRCB), THE DEVELOPER MUST OBTAIN A NOTICE OF INTENT (NOI) FROM THE SWRCB, WHICH ENCOMPASSES PREPARATION OF A STORM WATER POLLUTION PREVENTION PLAN (SWPPP), USE OF CONSTRUCTION BEST MANAGEMENT PRACTICES (BMPS) TO CONTROL STORM WATER RUNOFF QUALITY, AND BMP INSPECTION AND MAINTENANCE.

DEVELOPER MUST PROVIDE AN APPROVED EROSION CONTROL PLAN BY A REGISTERED CIVIL ENGINEER. THIS PLAN SHOULD INCLUDE ALL EROSION CONTROL 3MEASURES USED TO RETAIN MATERIALS ON SITE. EROSION CONTROL NOTES SHALL BE STATED ON THE PLANS.

EVERY 6 MONTHS, THE DEVELOPER SHALL SUBMIT A WORK SCHEDULE TO THE CITY TO SHOW THE TIMETABLE FOR ALL GRADING/EROSION CONTROL WORK IN CONJUNCTION WITH THIS PROJECT.

THE DEVELOPER MUST SUBMIT A TRAFFIC CONTROL PLAN BY A REGISTERED TRAFFIC ENGINEER TO BE APPROVED BY THE CITY. THE PLAN SHALL INCLUDE A TEMPORARY TRAFFIC CONTROL PLAN FOR WORK IN THE RIGHT OF WAY AS WELL AS A ROUTING PLAN FOR ALL VEHICLES USED DURING CONSTRUCTION. ALL TRAFFIC CONTROL SIGNS MUST BE REVIEWED AND APPROVED BY THE CITY PRIOR TO COMMENCEMENT OF WORK. THE CITY HAS ADOPTED MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD) STANDARDS FOR ALL SIGNAGE AND STRIPING WORK THROUGHOUT THE CITY.

STREET TREES SHALL BE PLANTED WITHIN THE PUBLIC RIGHT OF WAY TO THE SATISFACTION OF THE DIRECTOR OF PUBLIC WORKS AND SHALL BE OF A TYPE APPROVED BY THE CITY IN ACCORDANCE WITH ORDINANCE NO. 125.

FIRE SPRINKLERS SHALL BE INSTALLED IN ANY NEW CONSTRUCTION TO THE APPROVAL OF THE CITY.

A LETTER OF CLEARANCE FOR THE PROJECT SHALL BE OBTAINED FROM THE SANTA CLARA COUNTY FIRE DEPARTMENT PRIOR TO ISSUANCE OF BUILDING PERMITS. CLEARANCE SHOULD INCLUDE WRITTEN APPROVAL OF THE LOCATION OF ANY PROPOSED FIRE BACKFLOW PREVENTERS, FIRE DEPARTMENT CONNECTIONS AND FIRE HYDRANTS (TYPICALLY BACKFLOW PREVENTERS SHOULD BE LOCATED ON PRIVATE PROPERTY ADJACENT TO THE PUBLIC RIGHT OF WAY, AND FIRE DEPARTMENT CONNECTIONS MUST BE LOCATED WITHIN 100' OF A FIRE HYDRANT).

FIRE HYDRANTS SHALL BE LOCATED AS REQUIRED BY THE CITY AND SANTA CLARA COUNTY FIRE DEPARTMENT AS NEEDED.

PROVIDE SAN JOSE WATER COMPANY APPROVAL FOR WATER CONNECTION, SERVICE CAPABILITY AND LOCATION AND LAYOUT OF WATER LINES AND BACKFLOW PREVENTERS BEFORE ISSUANCE OF A BUILDING PERMIT APPROVAL.

DEVELOPER SHALL "QUIT CLAIM" TO THE CITY ALL RIGHTS TO PUMP, TAKE OR OTHERWISE EXTRACT WATER FROM THE UNDERGROUND BASIN OR ANY UNDERGROUND STRATA IN THE SANTA CLARA VALLEY.

A LETTER OF CLEARANCE FOR THE PROJECT SHALL BE OBTAINED FROM THE CUPERTINO SANITARY DISTRICT PRIOR TO ISSUANCE OF BUILDING PERMITS.

CLEARANCE APPROVALS FROM THE AGENCIES WITH EASEMENTS ON THE PROPERTY (INCLUDING PG&E, AT&T, AND SANTA CLARA VALLEY WATER DISTRICT, AND/OR EQUIVALENT AGENCIES) WILL BE REQUIRED PRIOR TO ISSUANCE OF

#### PUBLIC WORKS PROJECT CONDITIONS OF APPROVAL. EXCEPT FOR OTHERWISE NOTED, THE FOLLOWING CONDITIONS MUST BE COMPLETED AND/OR SUBMITTED PRIOR TO ISSUANCE OF BUILDING PERMIT.

DEVELOPER SHALL OFFER A 20-FOOT WIDE EASEMENT TO THE CITY FOR A FUTURE MULTI-USE TRAIL FACILITY ALONG THE EASTSIDE OF THE PROPERTY, AN INGRESS AND EGRESS EASEMENT FOR TRAIL MAINTENANCE ACCESS, AND A CONSTRUCTION ACCESS EASEMENT. THE DEDICATION SHALL BE PROCESS AT THE SAME TIME AS THE EASEMENT VACATION, IF ANY.

DEVELOPER SHALL INSTALL THE MULTI-USE TRAIL FACILITY, INSTALL AND MAINTAIN THE BRIDGE OVER THE PROPOSED INFILTRATION TRENCH, NEW WROUGHT IRON FENCE AND GATE FOR ACCESS BETWEEN THE FUTURE EASEMENT AND THE STORAGE FACILITY IN AREAS NOT LINED BY BUILDING TO THE SATISFACTION OF THE DIRECTOR OF PUBLIC WORKS, AND OTHER PUBLIC IMPROVEMENTS AND CONTRIBUTIONS AS AGREED UPON BY THE DEVELOPER AND DIRECTOR

THE PROJECT MAY BE SUBJECT TO APPLYING FOR A STREAMSIDE MODIFICATION PERMIT DUE TO ITS PROXIMITY TO THE JUNIPERO SERRA CHANNEL. THE PURPOSE OF THIS PERMIT IS TO ENSURE THAT THE PROJECT DOES NOT ADVERSELY IMPACT THE ADJACENT CHANNEL.

PROVIDE FRONTAGE IMPROVEMENTS ALONG THE PROJECT TO THE SATISFACTION OF THE DIRECTOR OF PUBLIC WORKS. STREET IMPROVEMENTS MAY INCLUDE, BUT NOT BE LIMITED TO, NEW DETACHED SIDEWALK, NEW ADA RAMP, DRIVEWAYS, STORM DRAIN LATERAL, STREET TREE INSTALLATIONS, AND STREET LIGHT AND/OR PEDESTRIAN PUSH BUTTON RELOCATION. ALL LAND CONTAINING PORTIONS OF PUBLIC SIDEWALK SHALL BE DEDICATED IN FEE TO THE

PUBLIC STREET WIDENING AND DEDICATIONS SHALL BE PROVIDED IN ACCORDANCE WITH CITY STANDARDS AND SPECIFICATIONS AND AS REQUIRED BY THE DIRECTOR OF PUBLIC WORKS.

CURBS AND GUTTERS, SIDEWALKS AND RELATED STRUCTURES SHALL BE INSTALLED IN ACCORDANCE WITH GRADES AND STANDARDS AS SPECIFIED BY THE DIRECTOR OF PUBLIC WORKS.

DEVELOPER SHALL PROVIDE PEDESTRIAN AND BICYCLE RELATED IMPROVEMENTS (E.G. WALKWAYS, BICYCLE RACKS, ETC.) CONSISTENT WITH THE CUPERTINO BICYCLE TRANSPORTATION PLAN AND THE PEDESTRIAN TRANSPORTATION PLAN, AND AS APPROVED BY THE DIRECTOR OF PUBLIC WORKS.

#### STREET LIGHTING INSTALLATION

STREET LIGHTING SHALL BE INSTALLED AND SHALL BE AS APPROVED BY THE DIRECTOR OF PUBLIC WORKS. LIGHTING FIXTURES SHALL BE POSITIONED SO AS TO PRECLUDE GLARE AND OTHER FORMS OF VISUAL INTERFERENCE TO ADJOINING PROPERTIES, AND SHALL BE NO HIGHER THAN THE MAXIMUM HEIGHT PERMITTED BY THE ZONE IN WHICH THE SITE IS LOCATED.

GRADING SHALL BE AS APPROVED AND REQUIRED BY THE DIRECTOR OF PUBLIC WORKS IN ACCORDANCE WITH CHAPTER 16.08 OF THE CUPERTINO MUNICIPAL CODE. 401 CERTIFICATIONS AND 404 PERMITS MAYBE REQUIRED. PLEASE CONTACT ARMY CORP OF ENGINEERS AND/OR REGIONAL WATER QUALITY CONTROL BOARD AS APPROPRIATE.

DRAINAGE SHALL BE PROVIDED TO THE SATISFACTION OF THE DIRECTOR OF PUBLIC WORKS. HYDROLOGY AND PRE- AND POST-DEVELOPMENT HYDRAULIC CALCULATIONS MUST BE PROVIDED TO INDICATE WHETHER ADDITIONAL STORM WATER CONTROL MEASURES ARE TO BE CONSTRUCTED OR RENOVATED. THE STORM DRAIN SYSTEM MAY INCLUDE, BUT IS NOT LIMITED TO, SUBSURFACE STORAGE OF PEAK STORMWATER FLOWS (AS NEEDED), BIORETENTION BASINS, VEGETATED SWALES, AND HYDRODYNAMIC SEPARATORS TO REDUCE THE AMOUNT OF RUNOFF FROM THE SITE AND IMPROVE WATER QUALITY. THE STORM DRAIN SYSTEM SHALL BE DESIGNED TO DETAIN WATER ON-SITE (E.G., VIA BURIED PIPES, RETENTION SYSTEMS OR OTHER APPROVED SYSTEMS AND IMPROVEMENTS) AS NECESSARY TO AVOID AN INCREASE OF THE TEN PERCENT FLOOD WATER SURFACE ELEVATION TO THE SATISFACTION OF THE DIRECTOR OF PUBLIC WORKS. ANY STORM WATER OVERFLOWS OR SURFACE SHEETING SHOULD BE DIRECTED AWAY FROM NEIGHBORING PRIVATE PROPERTIES AND TO THE PUBLIC RIGHT OF WAY AS MUCH AS REASONABLY POSSIBLE.

ALL STORM DRAIN INLETS SHALL BE CLEARLY MARKED WITH THE WORDS "NO DUMPING - FLOWS TO CREEK" USING PERMANENTLY AFFIXED METAL MEDALLIONS OR EQUIVALENT, AS APPROVED BY THE ENVIRONMENTAL PROGRAMS

C.3 REGULATED IMPROVEMENTS ARE REQUIRED FOR ALL PROJECTS CREATING AND/OR REPLACING 10,000

S.F. OR MORE OF IMPERVIOUS SURFACE (COLLECTIVELY OVER THE ENTIRE PROJECT SITE). THE DEVELOPER SHALL RESERVE A MINIMUM OF 4% OF DEVELOPABLE SURFACE AREA FOR THE PLACEMENT OF LOW IMPACT DEVELOPMENT MEASURES, FOR STORM WATER TREATMENT, UNLESS AN ALTERNATIVE STORM WATER TREATMENT PLAN, THAT SATISFIES C.3 REQUIREMENTS, IS APPROVED BY THE DIRECTOR OF PUBLIC WORKS.

THE DEVELOPER MUST INCLUDE THE USE AND MAINTENANCE OF SITE DESIGN, SOURCE CONTROL AND STORM WATER TREATMENT BEST MANAGEMENT PRACTICES (BMPS), WHICH MUST BE DESIGNED PER APPROVED NUMERIC SIZING CRITERIA. A STORM WATER MANAGEMENT PLAN, STORM WATER FACILITIES EASEMENT AGREEMENT, STORM WATER FACILITIES OPERATION AND MAINTENANCE AGREEMENT, AND CERTIFICATION OF ONGOING OPERATION AND MAINTENANCE OF TREATMENT BMPS ARE EACH REQUIRED.

ALL STORM WATER MANAGEMENT PLANS ARE REQUIRED TO OBTAIN CERTIFICATION FROM A CITY APPROVED THIRD PARTY REVIEWER.

THE PROJECT DEVELOPER SHALL ENTER INTO A DEVELOPMENT AGREEMENT WITH THE CITY OF CUPERTINO PROVIDING FOR PAYMENT OF FEES, INCLUDING BUT NOT LIMITED TO CHECKING AND INSPECTION FEES, STORM DRAIN FEES, PARK DEDICATION FEES AND FEES FOR UNDER GROUNDING OF UTILITIES. SAID AGREEMENT SHALL BE EXECUTED PRIOR TO ISSUANCE OF CONSTRUCTION PERMITS.

a. PLAN CHECK & INSPECTION FEES: PER CURRENT FEE SCHEDULE (\$7,389 OR 6% OF IMPROVEMENT COSTS)

PER CURRENT FEE SCHEDULE (\$3,059 OR 6% OF IMPROVEMENT COSTS)

c. STORM DRAINAGE FEE: PER CURRENT FEE SCHEDULE (\$9,566 PER AC) d. TRAFFIC IMPACT FEE: PER CURRENT FEE SCHEDULE (\$6,298 PER NEW PEAK-HOUR TRIP)

e. ENCROACHMENT PERMIT FEE: PER CURRENT FEE SCHEDULE (\$1,307)

f. STORM MANAGEMENT PLAN FEEPER CURRENT FEE SCHEDULE (\$1,396) g. STREAMSIDE PERMIT FEE: PER CURRENT FEE SCHEDULE (\$362)

h. EASEMENT VACATION FEE: PER CURRENT FEE SCHEDULE (\$3,522 PER APPLICATION)

FAITHFUL PERFORMANCE BOND: 100% OF OFF-SITE AND ON-SITE IMPROVEMENTS LABOR & MATERIAL BOND: 100% OF OFF-SITE AND ON-SITE IMPROVEMENT

#### ON-SITE GRADING BOND: 100% OF SITE IMPROVEMENTS

THE FEES DESCRIBED ABOVE ARE IMPOSED BASED UPON THE CURRENT FEE SCHEDULE ADOPTED BY THE CITY COUNCIL. HOWEVER, THE FEES IMPOSED HEREIN MAY BE MODIFIED AT THE TIME OF RECORDATION OF A FINAL MAP OR ISSUANCE OF A BUILDING PERMIT IN THE EVENT OF SAID CHANGE OR CHANGES, THE FEES CHANGED AT THAT TIME WILL REFLECT THE THEN CURRENT FEE SCHEDULE.

#### TRANSPORTATION IMPACT FEES

THE PROJECT IS SUBJECT TO THE PAYMENT OF TRAFFIC IMPACT FEES UNDER CITY'S TRANSPORTATION IMPACT FEE PROGRAM UNDER (CHAPTER 14.02 OF THE CUPERTINO MUNICIPAL CODE).

A BOUNDARY SURVEY AND A HORIZONTAL CONTROL PLAN WILL BE REQUIRED FOR ALL NEW CONSTRUCTION TO ENSURE THE PROPOSED BUILDING WILL BE SET BASED ON THE BOUNDARY SURVEY AND SETBACK REQUIREMENTS.

TRASH ENCLOSURE PLANS MUST BE DESIGNED IN ACCORDANCE WITH THE CITY'S "PUBLIC WORKS GUIDELINES POSTED AT WWW.CUPERTINO.ORG/NOWASTE, AND TO THE SATISFACTION OF THE ENVIRONMENTAL PROGRAMS MANAGER. CLEARANCE BY THE PUBLIC WORKS DEPARTMENT IS REQUIRED PRIOR TO OBTAINING A BUILDING PERMIT. (CMC 9.18.210 H & K)

DEVELOPER SHALL ENTER INTO AN OPERATIONS & MAINTENANCE AGREEMENT WITH THE CITY. THE AGREEMENT SHALL INCLUDE THE OPERATION AND MAINTENANCE FOR THE PROPOSED BRIDGE OVER THE PROPOSED INFILTRATION TRENCH, RETAINING WALLS, AND ANY NON-STANDARD APPURTENANCES IN THE PUBLIC RIGHT-OF-WAY THAT MAY INCLUDE, BUT IS NOT LIMITED TO, SIDEWALK, PAVERS, AND STREET LIGHTS.

DEVELOPER SHALL COMPLY WITH THE REQUIREMENTS OF THE UNDERGROUND UTILITIES ORDINANCE NO.

331 AND OTHER RELATED ORDINANCES AND REGULATIONS OF THE CITY OF CUPERTINO, AND SHALL COORDINATE WITH AFFECTED UTILITY PROVIDERS FOR INSTALLATION OF UNDERGROUND UTILITY DEVICES. DEVELOPER SHALL SUBMIT DETAILED PLANS SHOWING UTILITY UNDERGROUND PROVISIONS. SAID PLANS SHALL BE SUBJECT TO PRIOR APPROVAL OF THE AFFECTED UTILITY PROVIDER AND THE DIRECTOR OF PUBLIC WORKS.

ELECTRICAL TRANSFORMERS, TELEPHONE CABINETS AND SIMILAR EQUIPMENT SHALL BE PLACED IN UNDERGROUND VAULTS. THE DEVELOPER MUST RECEIVE WRITTEN APPROVAL FROM BOTH THE PUBLIC WORKS DEPARTMENT AND THE COMMUNITY DEVELOPMENT DEPARTMENT PRIOR TO INSTALLATION OF ANY ABOVE GROUND EQUIPMENT. SHOULD ABOVE GROUND EQUIPMENT BE PERMITTED BY THE CITY, EQUIPMENT AND ENCLOSURES SHALL BE SCREENED WITH FENCING AND LANDSCAPING SUCH THAT SAID EQUIPMENT IS NOT VISIBLE FROM PUBLIC STREET AREAS, AS DETERMINED BY THE COMMUNITY DEVELOPMENT DEPARTMENT. TRANSFORMERS SHALL NOT BE LOCATED IN THE FRONT OR SIDE BUILDING SETBACK AREA.

DOMESTIC AND FIRE WATER BACK FLOW PREVENTERS AND SIMILAR ABOVE GROUND EQUIPMENT SHALL BE PLACED AWAY FROM THE PUBLIC RIGHT OF WAY AND SITE DRIVEWAYS TO A LOCATION APPROVED BY THE CUPERTINO PLANNING DEPARTMENT, SANTA CLARA COUNTY FIRE DEPARTMENT AND THE WATER COMPANY.

YEAR OF FIRST PUBLICATION 2018 JORDAN ARCHITECTS, INC.

BAY AREA SELF STORAGE

CUPERTINO, CA

COA - PUBLIC WORKS THIS DRAWING AND ITS CONTENTS ARE INSTRUMENTS OF ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN



applicants must complete the PCB Screening Assessment Form to determine if the structure being demolished is deemed an applicable structure. No demolition permit will be issued until all required forms have been satisfactorily submitted and approved by the Environmental Programs Division.

The above requirements must be considered and discussed in advance with the project applicant and property owner. Other requirements may apply to your project and will be provided during formal plan review. Please note, if the trash enclosure will be displacing any parking spaces or changing the vehicular circulation on the site, a parking analysis and/or circulation plan must be provided to and approved by the Planning Division in advance of the trash enclosure plan submittal.

For additional questions, please contact the Environmental Programs Division at (408) 777-3354 or email at environmental@cupertino.org Additional information can be reviewed at www.cupertino.org/greendev

**Building/Demolition Permit Number** Development Permit Number Applicant Name/Title (Print) CURTIS LEIGH, PRINCIPAL Property Owner/Agent/Title (Print)

<sup>1</sup> The maintenance of each full capture device shall be adequate to prevent plugging, including plugging of the 5mm screen leading to trash overflow and bypass, flooding, or a full condition of the device's trash reservoir causing bypassing of trash. All full trash capture devices shall be inspected and maintained at least twice per year or to the manufacturer's minimum specifications at least three months or more apart, If any such device is found to have a plugged or blinded screen or is greater than 50 percent full of trash during a maintenance event or City inspection, the maintenance frequency shall be increased so that the device is neither plugged no more than half full of trash at the next

مائع ما ج

Rev. 1/19

Environmental Programs Division Conditions of Approval

during plan review. All full trash capture systems installed must be selected from the California State Water Resources Control Board approved list. Please refer to the Certified Trash Full Capture Systems List of Trash Treatment Control Devices to find a suitable system to treat the entire property. The design of the trash control system may be required to be reviewed and stamped by a registered Civil Engineer. Devices must be installed and maintained (cleaned) according to the manufacturer specifications and to ensure that they are operated at a level necessary to maintain their designation as a full-capture system as required by the City of Cupertino and San Francisco Bay Region Municipal Regional Stormwater Permit (NPDES No. CAS612008) Order No. R2-2015-0049 (MRP) Provision C.10.b.i. The property owner must provide official written record of cleaning and maintenance to the City upon request during periodic City inspections.

All exterior storm drain inlets on the property shall be clearly marked with "No Dumping Flows to Creek" or "No Dumping Flows to Bay".

#### **DESIGNATED SMOKING AREAS**

If smoking is permitted on the property, the designated smoking area(s) must be identified on the plans and an appropriate number of cigarette urns with rain water covers are required. If smoking is not permitted on the property an appropriate number of cigarette urns with rainwater covers must be provided on private property immediately adjacent to the sidewalk to prevent discarded cigarettes from being disposed on the sidewalk and

#### FOOD SERVICE ESTABLISHMENT INTERIOR WASTE PLAN

All wet waste businesses, defined as a business that produces food, organic and/or liquid wastes must identify on the plans, the location of all waste containers located within the kitchen/food preparation area. A minimum of two containers are required and shall be clearly labeled "food" and "non-food". More than two containers may be required based on the kitchen and food preparation area. The volume of all waste containers must be included with submittal.

The exterior use of copper for roofing materials, rain gutters, downspouts, or any ornamental enhancement is prohibited. Small copper adornments such as door handles or fence post caps are exempted.

#### **CONSTRUCTION AND DEMOLITION WASTE RECYCLING**

All construction, demolition, and renovation projects are required to submit a completed Waste Management Plan demonstrating that a minimum of 65% of the waste material generated is recycled consistent with the provisions of Cupertino Municipal Code Section 16.72. If a project includes both demolition and construction under separate permits, a waste recycling plan and report is required for each permit.

#### PCB ASSESSMENT AND MITIGATION IN ADVANCE OF DEMOLITION

If demolition of an existing building(s) is planned, PCB testing and remediation is required prior to obtaining a demolition permit. Buildings constructed or remodeled from January 1, 1950 to December 31, 1980 must undergo representative sample testing and analysis by a certified analytical laboratory for PCB presence. A report of these findings must be submitted to the Environmental Programs Division. This requirement does not apply to remodeling and single-family residential and/or wood frame structures: however, <u>all</u> demolition permit

Rev. 1/19



#### ENVIRONMENTAL PROGRAMS DIVISION

10300 TORRE AVENUE • CUPERTINO, CA 95014-3255 TELEPHONE: (408) 777-3354 • FAX: (408) 777-3333 CUPERTINO.ORG

#### ENVIRONMENTAL PROGRAMS DIVISION CONDITIONS OF APPROVAL FOR TENANT IMPROVEMENTS AND DEVELOPMENT

To conform with the Cupertino Municipal Code and State of California water quality standards for the San Francisco Bay region, new and redeveloped properties are required to install exterior/interior site improvements, modify existing structures, meet construction/demolition waste diversion requirements, and identify/mitigate certain pollutants of concern from demolition projects. Frequently, a tenant improvement or modification of an existing use triggers the requirement for construction of a covered trash enclosure, installation of exterior public waste receptacles (trios and cigarette urns), storm drain full trash capture systems, and other requirements. These improvements are a condition of approval that the property owner and the tenant must discuss with City Environmental Programs staff prior to permit issuance to ensure that the property owner and tenant have agreed on the source of funding and operations/maintenance for the required improvements. Depending on your project, any number of the requirements below may apply and should be considered during your project planning. Upon formal submittal of the project scope and plans, there will be review and comment provided from the Environmental Programs Division staff specific to your project.

All wet waste businesses, defined as a business that produces food, organic and/or liquid wastes, must include a covered trash enclosure to accommodate all waste containers including compactors (landfill, recycling, organics, and cooking oil/grease). The trash enclosure must be designed and constructed in accordance with the "Guidelines for Non-Residential Building Trash and Recycling Enclosures". If a property does not have a trash enclosure, has one that does not have roof, or is of inadequate size for all tenant space on the property, construction of a new or modification of an existing one must be included with the plan set submitted during the review process. The trash enclosure must be designed or modified to accommodate all waste containers in use by all occupants of the property, not merely the tenant making application for the building or development

#### WASTE TRIOS AND CIGARETTE URNS

One permanently installed exterior waste receptacle trio (landfill, recycle, compost) and cigarette urn, designed for public use must be installed on the property and shown on the plans submitted. One trio set and cigarette urn satisfies the requirement for up to four adjacent businesses on one property. The receptacle openings and cigarette urn must be sufficiently covered to prevent rainwater intrusion.

#### FULL TRASH CAPTURE STORM DRAIN SYSTEMS

For projects located in moderate and high trash management areas as defined by the City of Cupertino Trash Management Area Map or are adjacent to a creek, full trash capture systems are be required. Fueling stations, automotive, light industrial or other uses which may have fine particulate or liquid based pollutants (including cooking oils/grease) may require an additional media and/or hydrocarbon filter fitted to the trash capture system. Topographical flow maps of the property identifying all storm drain inlets, underground storm water flow lines, and all connections with the City's storm drain system and any adjacent property are required to be submitted

BAY AREA SELF STORAGE

COA - ENVIRONMENTAL PROG. DIV ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE

REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN

ARCHITECTS, II

In the Santa Clara Valley, storm drains flow directly to our local creeks, and on to San Francisco Bay, with no treatment.

Storm water pollution is a serious problem for wildlife dependent on our waterways and for the people who live near polluted streams or baylands.

Proper management of construction sites reduces pollution significantly.

This sheet summarizes the "Best Management Practices" (BMPs) for storm water pollution prevention.

#### ORDINANCE OF THE CITY OF CUPERTINO FOR STORM WATER POLLUTION PREVENTION & WATERCOURSE PROTECTION: Chapter 9.18

#### 9.18.040 Discharge into the storm drain prohibited

It is unlawful to cause, allow, or permit to be discharged, any discharge not composed entirely of stormwater to the storm drain system or to surface waters or to any location where it would contact or eventually be transported to surface waters, including flood plain areas, unless specifically called out in the Municipal Regional Permit as an exempt or conditionally exempt discharge.

#### 9.18.070 Accidental Discharge

All persons shall notify the Director of Public Works immediately upon accidentally discharging pollutants of concern to enable countermeasures to be taken by the City to minimize damage to storm drains and the receiving waters. Initial notification shall be followed, within five (5) business days of the date of occurrence, by a detailed written statement describing the causes of the accidental discharge and the measures being taken to prevent future occurrences. Such notification will not relieve persons of liability for violations of this chapter or for any fines imposed on the City on account thereof under Section 13350 of the California Water Code, or for violation of Section 5650 of the California Fish and Wildlife Code, or any other applicable provisions of State or Federal laws.

#### 9.18.220 Violation\*

Any person who violates any provision of this Chapter shall be guilty of a misdemeanor and upon conviction thereof shall be punished as provided in Chapter 1.12 of the City of Cupertino Municipal Code.

Chapter 1.12: General Penalty, Section 1.12.010, paragraph D, states\*:

Unless otherwise specified by this code, an infraction is punishable by:

- A fine not to exceed \$100 for a first violation
- A fine not to exceed \$200 for a second violation A fine not to exceed \$500 for a third violation of
- the same chapter within one year.

#### 9.18.240 Civil penalty for illicit discharges\*

Any person who discharges pollutants, in violation of this Chapter, by the use of illicit connections shall be civilly liable to the City in a sum **not to exceed twenty-five thousand** dollars per day per violation for each day in which such

\*Excerpts – For complete CODE language refer to the City of Cupertino Municipal Code.

> **Building Dept:** 408-777-3228 Public Works Dept: 408-777-3354 Santa Clara County Recycling Hotline: 800-533-8414 www.reducewaste.org www.recyclestuff.com Small Business Hazardous Waste: 408-299-7300 Cupertino Sanitary Sewer Distr 408-253-7071 Santa Clara Valley Urban Runoff Pollution Prevention Prgm 800-794-2482 State Office of Emergency Services 1-800-852-7550 (24 hrs)

Report spills to 911

DIRECTOR OF PUBLIC WORKS

#### General Construction and Site Supervision

#### Storm Drain Pollution from Construction Activities

Construction sites are common sources of storm water pollution. Materials and wastes that blow or wash into a storm drain, gutter, or street have a direct impact on local creeks and the Bay. As a contractor, or site supervisor, owner or operator of a site, you may be responsible for any environmental damage caused by your subcontractors or employees.

- ☐ Keep an orderly site and ensure good housekeeping practices are used.
- Maintain equipment properly. Cover materials when they are not in use. Keep materials away from streets, storm
- drains and drainage channels. Ensure dust control water doesn't leave site
- or discharge to storm drains. Advance Planning To Prevent Pollution
- Schedule ex cavation and grading activities for dry weather periods. To reduce soil erosion, plant temporary vegetation or place other erosion controls before rain begins. Use the Erosion and Sediment Control Manual, available from the Regional Water Quality Control Board, as a reference.
- Control the amount of runoff crossing your site (especially during excavation!) by using berns or temporary or permanent drainage ditches to divert water flow around the site Reduce stormwater runoff velocities by constructing temporary check dams or bems
- where appropriate Train your employees and subcontractors. The city can provide brochures about these issues for you to distribute to workers at your construction site. Inform your subcontra dors about the stomwater requirements and their own responsibilities. Use Blueprint for a Clear Bay, a construction best management ractices guide available at our Building Dept. counter.

#### Good Housekeeping Practices

- Designate one area of the site for auto parking. vehicle refueling, and routine equipment maintenance. The designated area should be well away from streams or storm drain inlets, bermed if necessary. Make major repairs off site. To prevent off-site tracking of dirt, provide entrances with stabilized aggregate surfaces. Or
- provide a tire wash area. ☐ Keep materials out of the rain – prevent runoff contamination at the source. Cover exposed piles of soil or construction materials with plastic sheeting or temporary roofs. Before it rains, sweep and remove materials from surfaces that drain to
- storm drains, creeks, or channels. Contain all litter, food wrappers, bottles and cans - Place lidded trash and recycling bins
- around the site. Clean up leaks, drips and other spills
- immediately so they do not contaminate soil or groundwater or leave residue on paved surfaces. Use dry cleanup methods whenever possible. If you must use water, use just enough to keep the
- Cover and maintain dumpsters. Place dumpsters under roofs or cover with tarps or plastic sheeting secured around the outside of the dumpster. Never clean out a dumpster by hosing it down on the construction site.
- ☐ Place portable toilets away from storm drains. Make sure portable toilets are in good working order. Check frequently for leaks.
- Materials/Waste Handling ☐ Practice Source Reduction -- minimize waste
- when you order materials. Estimate carefully. Recycle excess materials, whenever possible. such as concrete, asphalt, scrap metal, solvents, degreasers, cleared vegetation, paper, rock, and vehicle maintenance materials such as used oil. antifreeze, batteries, and tires: www.reducewaste.org for info
- Dispose of all wastes properly. Materials that cannot be recycled must be taken to an appropriate landfill or disposed of as hazardous waste. Never bury waste materials or leave then in the street or near a creek or stream bed.
- In addition to local grading and building permits, you will need to obtain coverage under the State's General Construction Activity Stormwater Permit if your construction site's disturbed area totals 5 acres or more. Information on the General Permit can be obtained from the Regional Water Quality Control Board. (This criteria will change to one

#### Landscaping, Gardening, and Pool Maintenance

#### Lands caping/Garden Maintenance

- Protect stockpiles and landscaping materials from wind and rain by storing them under tarps or secured plastic sheeting.
- Schedule grading and excavation projects during dry weather

Protect storm drains with sandbags, gravel-

filled bags, straw wattles, or other sediment

- Use temporary check dams or ditches to divert runoff away from storm drains.
- Re-vegetation is an excellent form of erosion control for any site
- ☐ Store pesticides, fertilizers, and other chemicals indoors or in a shed or storage
- Use pesticides sparingly, according to instructions on the label. Rinse empty containers, and use rinsewater as product Dispose of rinsed, empty containers in the trash. Dispose of unused pesticides as
- In Cupertino, residents with curbside recycling can collect lawn, garden and tree trimmings in yardwaste toters. Yardwaste will be collected and composted by the city's contractors. Residents are encouraged to compost vardwaste on-site themselves. Or take yard waste to a land fill where it will be composted
- ☐ Landscape contractors should take clippings and pruning waste to a landfill that composts yard waste (BFI's Newby Island and Zanker Rd. landfill are the nearest)
- Do not blow or rake leaves into the street

#### Storm Drain Pollution from Landscaping and Swimming Pool Maintenance Many landscaping activities expose soils and

increase the likelihood that earth and garden chemicals will run off into the storm drains during irrigation or when it rains. Swimming pool water containing chlorine and copper-based algaecides should never be discharged to storm drains. These chemicals are toxic to aquatic life.

#### Pool/Fountain/Spa Maintenance

#### Draining pools or spas

When it's time to drain a pool, spa, or fountain please be sure to call the Cupertino Sanitary District before you start for further guidance on flow rate restrictions, backflow prevention, and handling special cleaning waste (such as acid wash). Discharge flows should be kept to the low levels typically possible through a garden hose Higher flow rates may be prohibited by local ordinance.

- ☐ Never discharge pool or spa water to a street or storm drain; discharge to a sanitary sewer cleanout
- ☐ If possible, when emptying a pool or spa, let chlorine dissipate for a few days and then recycle/reuse water by draining it gradually onto a landscaped area.
- Do not use copper-based algaecides Control algae with chlorine or other alternatives, such as sodium bromide. Filter Cleaning
- ☐ Never clean a filter in the street or near a storm drain. Rinse cartridge and diatomaceous earth filters onto a dirt area. and spade filter residue into soil. Dispose of spent diatomaceous earth in the garbage.
- ☐ If there is no suitable dirt area, call Cupertino Sanitary for instructions on discharging filter backwash or rinsewater to the sanitary sewer.

#### Earth-Moving **Activities**

#### Storm Drain Pollution from Earth-Moving Activities

Soil excavation and grading operations loosen large amounts of soil that can flow or blow into storm crains when handled improperly. Sediments in runoff can clog storm drains, smother aquatic life, and destroy habitats in creeks and the Bay. Effective erosion control practices reduce the amount of runof crossing a site and slow the flow with check dams o roughened ground surfaces.

#### Practices During Construction

- Remove existing vegetation only when absolutely necessary. Plant temporary vegetation for erosion control on slopes or where construction is not immediately planned.
- Protect downslope drainage courses, streams, and storm drains with wattles, or temporary drainage swales. Use check dams or ditches to divert runoff around excavations. Refer to the Regional Water Quality Control Board's Erosion and Sediment Control Field Manual for proper erosion and sediment control measures.
- ☐ Cover stockpiles and excavated soil with secured tarps or plastic sheeting.



#### Dewatering Operations

#### Storm Drain Pollution From Dewatering Activities

Be sure to call your city's storm water inspector at 408-472-9907 before discharging water to street, gutter, or storm drain. Filtration or diversion through a basin, tank, and sediment trap may be required. Reuse water for dust control, irrigation or another on-site purpose to the greatest extent

#### Check for Sediment or Toxic Pollutants

- ☐ Check for odors, discoloration, or an oily sheen on ground water.
- Ask your city inspector whether the groundwater must be tested by a certified laboratory
- Depending on the test results, you may be allowed to discharge pumped groundwater to the storm drain OR you may be required to discharge to the sanitary sewer or collect and haul the water off-site for treatment and disposal at an appropriate treatment facility.
- ☐ When discharging to a storm drain, protect the inlet using a barrier of burlap bags filled with drain rock, or cover inlet with filter fabric anchored under the grate.
- ☐ Contact Cupertino Sanitary District at 253-7071 prior to discharging to the sanitary sewer.

The Project Contractor is responsible

located within the Public Right of Way

for removal of all BMP Facilities

upon project final inspection.

#### Heavy Equipment Operation

Storm water Pollution from Heavy Equipment on Construction Sites Poorly maintained vehicles and heavy equipment that leak fuel, oil, antifreeze or other fluids on the construction site are common sources of storm drain pollution Prevent spills and leaks by isolating

equipment from runoff channels, and by

watching for leaks and other maintenance

problems. Remove construction equipment

#### Site Planning and Preventive Vehicle Maintenance

from the site as soon as possible.

- ☐ Designate one area of the construction site, well away from streams or storm drain inlets, for auto and equipm ent parking, refueling, and routine vehicle and equipment maintenance. Contain the area with berms, sand bags, or other
- Maintain all vehicles and heavy equipment.
- Perform major maintenance, repair jobs, and vehicle and equipment washing off-site, where
- If you must drain and replace motoroil, radiator coolant, or other fluids on site, use drip pans or drop cloths to catch drips and spills. Collect all spent fluids, store in separate containers, and properly dispose as hazardous waste (recycle
- Do not use diesel oil to lubricate equipment parts, or clean equipment. Use only water for any onsite cleaning.
- O cover exposed fifth wheel hitches and other oily or greasy equipment during rain events.

#### Spill Cleanup

#### Clean up spills im mediately.

- ☐ Neverhose down "dirty" payement or im permeable surfaces where fluids have spilled Use dry cleanup methods (absorbent materials, cat litter, and/or rags) whenever possible and properly dispose of absorbent
- ☐ Sweep up spilled dry materials immediately. Never attempt to "wash them away" with water,
- Use as little water as possible for dust control. Ensure water used doesn't leave silt or
- ☐ Clean up spills on dirt areas by digging up and properly disposing of contaminated soil
- ☐ Call 911 for significant spills ☐ If the spill poses a significant hazard to hum an health and safety, property or the

State Office of Emergency Services.

The property owner and the contractor share ultimate responsibility for the activities that occur on a construction site. You may be held responsible for any environmental damage caused by your subcontractors or employees.

#### Painting and Application of Solvents and Adhesives

#### Storm Drain Pollution from Paints,

Solvents, and Adhesives All paints, solvents, and adhesives contain chemicals that are harmful to wildlife in local creeks, San Francisco Bay, and the Pacific Ocean. Toxic chemicals may come from liquid or solid products or from cleaning residues or rags. Paint material and wastes, adhesives and cleaning fluids should be recycled when possible, or disposed of properly to prevent these materials from flowing into storm drains and watercourses.

#### Handling Paint Products

Keep all liquid paint products and wastes away from the gutter, street, and storm

#### Painting Cleanup

- Never clean brushes or rinse paint containers into a street, gutter, storm drain, French drain, or creek.
- ☐ For water-based paints, paint out brushes to the extent possible, and rinse into an inside sink drain that goes to the sanitary sewer.
- For oil-based paints, paint out brushes to the extent possible and clean with thinner or solvent. Filter and reuse thinners and solvents where possible. Dispose of excess liquids and residue as hazardous waste.

☐ When thoroughly dry, empty paint cans, used

brushes, rags, and drop doths may be

disposed of as garbage.

#### Paint Removal

- ☐ Paint chips and dust from non-hazardous dry stripping and sand blasting may be swept up or collected in plastic drop cloths and disposed of as trash.
- ☐ Chemical paint stripping residue, and chips and dust from marine paints, or paints containing lead, mercury or tributyl tin must be disposed of as hazardous wastes. Lead based paint removal requires a state-certified contractor.
- ☐ When stripping or cleaning building exteriors with high-pressure water, block storm drains. Direct washwater onto a dirt area and spade into soil. Or, check with Cupertino Sanitary District to find out if you can mop or vacuum the washwater and dispose of it in a sanitary sewer drain. Sampling of the washwater may be required.
- Washwater from painted buildings constructed before 1978 can contain high amounts of Lead, even if paint chips are not present. Before you begin stripping paint or cleaning pre-1978 building exteriors with water under high pressure, test paint for lead by taking paint scrapings to a local laboratory. (See Yellow Pages for a state-certified
- ☐ If there is loose paint on the building, or if the paint tests positive for lead, block storm drains. Check with Cupertino Sanitary District to determine whether you may discharge water to the sanitary sewer, or if you must send it offsite for disposal as hazardous waste.

#### Paint Disposal, Return or Donation

- ☐ Dispose of unwanted liquid paint, thinners. solvents, glues, and deaning fluids as hazardous waste (call the Small Business Hazardous Waste Prgm: 299-7300).
- ☐ Or Return to supplier. (Unopened cans of paint may be able to be returned. Check with the vendor regarding its "buy-back" policy.)
- ☐ Donate excess paint (call 299-7300 to donate.)

#### Roadwork and Paving

Develop and implement erosion/sediment control plans for roadway embankments.

☐ Schedule excavation and grading work during

General Business Practices

- Check for and repair leaking equipment. Perform major equipment repairs at designated areas in your maintenance yard.
- equipment repairs at construction sites. ☐ When refueling or when vehicle /e quipment maintenance must be done on site, designate a

where cleanup is easier. Avoid performing

- location away from storm drains and creeks. Do not use diesel oil to lubricate equipment parts or clean equipment.
- Recycle used oil, concrete, broken asphalt, etc. whenever possible, or dispose of properly. (www.recyclestuff.com for list of recycling companies.)

#### Asphalt/Concrete Removal

Avoid creating excess dust when breaking asphalt or concrete.

possible. Shovel or vacuum saw-cut slurry and

truck. Do not dump vacuumed liquor in storm

- After breaking up old pavement, be sure to remove all chunks and pieces. Make sure broken pavement does not come in contact with rainfall or runoff. ☐ When making saw cuts, use as little water as
- remove from the site. Cover or protect storm drain inlets during saw-cutting. Sweep up, and properly dispose of, all residues. Sweep, never hose down streets to clean up tracked dirt. Use a street sweeper or vacuum

Road paving, surfacing, and pavement removal happen right in the street, where there are numerous opportunities for a sphalt, saw-cut slurry, or excavated material to illegally enter storm drains. Extra planning is required to store and dispose of materials properly and guard against pollution of storm drains, creeks, and the Bay.

Storm Drain Pollution

from Roadwork

#### **During Construction**

- Avoid paving and seal coating in wet weather, or when rain is forecast, to prevent fresh materials from contacting stormwater
- ☐ Cover and seal catch basins and manholes when applying seal coat, slurry seal, fog seal, or similar materials. Protect drainage ways by using earth dikes,
- sand bags, or other controls to divert or trap and filter runoff. ■ Never wash excess material from exposedaggregate concrete or similar treatments into a street or storm drain. Collect and recycle, or
- dispose to dirt area. ☐ Cover stockpiles (asphalt, sand, etc.) and other construction materials with plastic tarps. Protect from rainfall and prevent runoff with temporary roofs or plastic sheets and berms
- absorbent material (cloth, rags, etc.) to catch drips when not in use. ☐ Clean up all spills and leaks using "dry" methods (with absorbent materials and/or rags), or dig up, remove, and properly dispose

☐ Park paving machines over drip pans or

☐ Collect and recycle or appropriately dispose of excess abrasive gravel or sand. ???

of contaminated soil.

Avoid over-application by water trucks for dust

#### Fresh Concrete and Mortar Application -

#### Storm Drain Pollution from Fresh Concrete and Mortar Applications

Fresh concrete and cement-related mortars that wash into lakes, streams, or estuaries are toxic to fish and the aquatic environment. Disposing of these materials to the storm drains or creeks can block storm drains, causes serious problems, and is prohibited by law.

#### General Business Practices

- ☐ Wash out concrete mixers only in designated washout areas in your yard, away from storm drains and waterways, where the water will flow into a temporary waste pit in a dirt area. Let water percolate through soil and dispose of settled, hardened concrete as garbage. Whenever possible, recycle washout by
- pumping back into mixers for reuse. Wash out chutes onto dirt areas that do not flow to streets or drains.
- Always store both dry and wet materials under cover, protected from rainfall and runoff and away from storm drains or waterways. Protect dry materials from wind.

Secure bags of cement after they are open.

away from streets, gutters, storm drains,

Be sure to keep wind-blown cement powder

rainfall, and runoff. Do not use diesel fuel as a lubricant on concrete forms, tools, or trailers.

#### **During Construction**

- Don't mix up more fresh concrete or cement than you will use in a two-hour period.
- ☐ Set up and operate small mixers on tarps or heavy plastic drop cloths. ☐ When cleaning up after driveway or sidewalk construction, wash fines onto dirt areas, not
- down the drive way or into the street or storm ☐ Protect applications of fresh concrete and mortar from rainfall and runoff until the
- material has dried. Wash down exposed aggregate concrete only when the washwater can (1) flow onto a dirt area, (2) drain onto a bermed surface from which it can be pumped and disposed of properly, or (3) be vacuumed from a catchment created by blocking a storm drain inlet. If necessary, divert runoff with temporary berms.
- Make sure run off does not reach gutters or ☐ When breaking up pavement, be sure to pick up all the pieces and dispose of properly. Recycle large chunks of broken concrete. See
- www.reducewaste.org for info on recyclers. ■ Never bury waste material. Dispose of small amounts of excess dry concrete, grout, and mortar in the trash.
- ☐ Never dispose of washout into the street, storm drains, drainage ditches, or streams.



#### **Small Business Hazardous Waste** Disposal Prgm

Businesses that generate less than 27 gallons or 220 pounds of hazardous waste per month are eligible to use this program. Call 408-299-7300 for a quote.





**UPDATED SEPTEMBER 2016** 


#### 91/16 CONSTRUCTION BEST MANAGEMENT PRACTICES

DEPARTMENT OF PUBLIC WORKS







SHEET:









**KEY NOTES** 

1 PROPERTY LINE.

20' WIDE ACCESS GATES IN ACCORDANCE WITH CFC, SECTION 503 AND APPENDIX D

3 ACCESS KEY PAD W/ KNOX BOX.

4 FIRE HYDRANT. UNOBSTRUCTED CLEAREANCE= 15' EITHER SIDE OF HYDRANT

20' CLEAR FIRE APPARATUS ACCESS ROAD. MARKED "FIRE LANE" AS ZEROUIRED.

6 RESIDENCE ACCESS PATH. 7' CLEAR GROUND-LADDER RESCUE AREA 7 PROPERTY IDENTIFICATION NUMBER PLACED ON BUILDING PARAPET

2-HOUR FIRE RESISTANCE WALL, BLDG. 'B' ONLY, ALONG PROPERTY LINE. 30" MIN. PARAPET FROM TOP OF ROOF DECK REQUIRED

9 PROPOSED 20 FEET GATE ACCESS FOR TRAIL MAINTENANCE TO SERVE AS SECOND EMERGENCY ACCESS. KNOX KEY SWITCH WILL BE PROVIDED.

10 FIRE TRUCK TRAVEL PATH.

11 FIRE RISER ROOM

12 F.D.C. LOCATION.

13 STANDPIPE LOCATION.

#### FIRE NOTES

- THE OWNER(S), OCCUPANT(S) AND ANY CONTRACTOR(S) OR SUBCONTRACTOR(S) ARE RESPONSIBLE FOR CONSULTING WITH THE WATER PURVEYOR OF RECORD IN ORDER TO DETERMINE IF ANY MODIFICATION OR UPGRADE OF THE EXISTING WATER SERVICE IS REQUIRED. A STATE OF CALIFORNIA LICENSED (C-16) FIRE PROTECTION CONTRACTOR SHALL SUBMIT PLANS CALCULATIONS, A COMPLETED PERMIT APPLICATION AND APPROPRIATE FEES TO THIS DEPARTMENT FOR REVIEW AND APPROVAL PRIOR TO BEGINNING THEIR WORK. CFC SEC. 903.2 AS ADOPTED AND AMENDED BY CUPMC.
- POTABLE WATER SUPPLIES SHALL BE PROTECTED FROM CONTAMINATION CAUSED BY FIRE PROTECTION WATER SUPPLIES. IT IS THE RESPONSIBILITY OF THE APPLICANT AND ANY CONTRACTORS AND SUBCONTRACTORS TO CONTACT THE WATER PURVEYOR SUPPLYING THE SITE OF SUCH PROJECT, AND TO COMPLY WITH THE REQUIREMENTS OF THAT PURVEYOR. SUCH REQUIREMENTS SHALL BE INCORPORATED INTO THE DESIGN OF ANY WATER-BASED FIRE CONTAINERS THAT MAY BE PHYSICALLY CONNECTED IN ANY MANNER TO AN APPLIANCE CAPABLE
- OF CAUSING CONTAMINATION OF THE POTABLE WATER SUPPLY OF THE PURVEYOR OF RECORD. TIMING OF INSTALLATION. WHEN FIRE APPARATUS ACCESS ROADS OR A WATER SUPPLY FOR FIR PROTECTION IS REQUIRED TO BE INSTALLED, SUCH PROTECTION SHALL BE INSTALLED AND MADE SERVICEABLE PRIOR TO AND DURING THE TIME OF CONSTRUCTION EXCEPT WHEN APPROVED ALTERNATIVE METHODS OF PROTECTION ARE PROVIDED. TEMPORARY STREET SIGNS SHALL BE INSTALLED AT EACH STREET INTERSECTION WHEN CONSTRUCTION OF NEW ROADWAYS ALLOWS PASSAGE BY VEHICLES IN ACCORDANCE WITH SECTION 505.2 CFC SEC. 501.4.
- NEW AND EXISTING BUILDINGS EQUIPPED WITH FIRE ALARM SYSTEM IN ACCORDANCE WITH NFPA 72 AND REFER TO CFC SEC. 907.
- CONSTRUCTION SITE FIRE SAFETY: ALL CONSTRUCTION SITES MUST COMPLY WITH APPLICABLE PROVISIONS OF THE CFC CHAPTER 33 AND OUR STANDARD DETAIL AND SPECIFICATION SI-7 PROVIDE APPROPRIATE NOTATIONS ON SUBSEQUENT PLAN SUBMITTALS, AS APPROPRIATE TO
- NEW AND EXISTING BUILDINGS EQUIPPED WITH AUTOMATIC FIRE SPRINKLER SYSTEM I ACCORDANCE WITH NFPA 13.
- REQUIRED FIRE ACCESS EXCEPTION:PROJECTS HAVING A PER BUILDING GROSS AREA OF UP TO

- IMPROVEMENT OF THE EXISTING PUBLIC SAFETY COMMUNICATION SYSTEMS. REFER TO CFC SEC

- CALCULATIONS, A COMPLETED PERMIT APPLICATION AND APPROPRIATE FEES TO THIS ADOPTED AND AMENDED BY CUPMC.
- FIRE ALARM SYSTEM TO BE PROVIDED. UNDER DEFERRED SUBMITTAL

BAY AREA SELF STORAGE

SERVICE AND ARE THE COPYRIGHTED PROPERTY OF JORDAN ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE PROJECT NOTED ABOVE AND MAY NOT BE REUSED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN YEAR OF FIRST PUBLICATION 2018 JORDAN ARCHITECTS, INC


1 CALLE IGLESIA, SUITE 1 SAN CLEMENTE,

jordan

**ARCHITECTS, INC** 


CUPERTINO, CA





CUPERTINO, CA


THIS DRAWING AND ITS CONTENTS ARE INSTRUMENTS OF SERVICE AND ARE THE COPYRIGHTED PROPERTY OF JORDAN ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE PROJECT NOTED ABOVE AND MAY NOT BE REUSED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF JORDAN ARCHITECTS, INC. "COPYRIGHT" YEAR OF FIRST PUBLICATION 2018 JORDAN ARCHITECTS, INC.



BAY AREA SELF STORAGE

SERVICE AND ARE THE COPYRIGHTED PROPERTY OF JORDAN ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE

REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF JORDAN ARCHITECTS, INC. "COPYRIGHT"




BAY AREA SELF STORAGE CUPERTINO, CA

PRELIM. FLOOR PLAN

SERVICE AND ARE THE COPYRIGHTED PROPERTY OF JORDAN ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE PROJECT NOTED ABOVE AND MAY NOT BE REUSED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF JORDAN ARCHITECTS, INC. "COPYRIGHT" YEAR OF FIRST PUBLICATION 2018 JORDAN ARCHITECTS, INC.





**KEY NOTES** PROJECTION OF 2ND & 3RD FLOOR ABOVE. 2 EXTERIOR DOOR. 3 PRELIMINARY COLUMN LOCATION 4 CANOPY PROJECTION ABOVE. 5 | PROJECTION ABOVE. 6 EXTERIOR WALL. SEE ELEVATIONS FOR FINISH. 7 CANOPY PROJECTION BELOW. 8 WINDOW / ALUMINUM STOREFRONT 9 INTERIOR PARTITION 10 UNIT ROLL-UP DOOR 11 FAUX ROLL-UP DOOR 12 DETECTABLE WARNING. 13 LOADING AREA BELOW. 14 F.D.C. STAND PIPE 15 RESTROOM. WALL LEGEND — EXTERIOR WALL & SHAFT WALLS PARTITION WALL / LOAD BEARING 2-6" MAXIMUM TRAVEL DISTANCE TO BATHROOM LOCATED ON SECOND FLOOR IS 225 FEET, INCLUDING VERTICAL DISTANCE BETWEEN FLOORS **KEY PLAN** OFFICE & METEOR DR.

# BAY AREA SELF STORAGE


PRELIM. FLOOR PLAN


THIS DRAWING AND ITS CONTENTS ARE INSTRUMENTS OF SERVICE AND ARE THE COPYRIGHTED PROPERTY OF JORDAN ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE PROJECT NOTED ABOVE AND MAY NOT BE REUSED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF JORDAN ARCHITECTS, INC. "COPYRIGHT" YEAR OF FIRST PUBLICATION 2018 JORDAN ARCHITECTS, INC.


JOB NUMBER: 17-60 SCALE: 1/16"=1'-0 DATE: 01/25/20 131 CALLE IGLESIA, SUITE 1
SAN CLEMENTE,
CA 92672-7541
Telephone 949/388-8090
Facsimile 949/388-8290


jordan

CUPERTINO, CA










# BAY AREA SELF STORAGE


PRELIM. FLOOR PLAN


THIS DRAWING AND ITS CONTENTS ARE INSTRUMENTS OF SERVICE AND ARE THE COPYRIGHTED PROPERTY OF JORDAN ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE PROJECT NOTED ABOVE AND MAY NOT BE REUSED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF JORDAN ARCHITECTS, INC. "COPYRIGHT" YEAR OF FIRST PUBLICATION 2018 JORDAN ARCHITECTS, INC.

17-606 16"=1'-0" 1/25/2021










EXISTING BUILDING D
UNIT COUNT = 52 UNITS

BUILDING C

UNIT COUNT = 8 UNITS




# BAY AREA SELF STORAGE

PRELIM. FLOOR PLAN

THIS DRAWING AND ITS CONTENTS ARE INSTRUMENTS OF SERVICE AND ARE THE COPYRIGHTED PROPERTY OF JORDAN ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE PROJECT NOTED ABOVE AND MAY NOT BE REUSED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF JORDAN ARCHITECTS, INC. "COPYRIGHT" YEAR OF FIRST PUBLICATION 2018 JORDAN ARCHITECTS, INC.

JOB NUMBER: 17-60 SCALE: 1/16"=1'-0 DATE: 01/25/202






#### **KEY NOTES**

- 1 STANDING SEAM METAL ROOF.
- 2 DOWNSPOUT
- 3 GUTTE
- 4 TPO ROOFING SYSTEM.
- 5 ROOF DRAIN & OVERFLOW.
- 6 ROOF ACCESS HATCH.
- 7 ELEVATOR PENTHOUSE.
- 8 TYPICAL PARAPET.

#### **GENERAL NOTES**

1. COPPER METAL ROOFING, COPPER GRANULE CONTAINING ASPHALT SHINGLES, COPPER GUTTERS AND DOWNSPOUTS, AND / OR OTHER EXTERIOR ORNAMENTAL COPPER ARE NOT PERMITTED FOR USE ON ANY COMMERCIAL OR INDUSTRIAL BUILDING.



# BAY AREA SELF STORAGE

CUPERTINO, CA




THIS DRAWING AND ITS CONTENTS ARE INSTRUMENTS OF SERVICE AND ARE THE COPYRIGHTED PROPERTY OF JORDAN ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE PROJECT NOTED ABOVE AND MAY NOT BE REUSED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF JORDAN ARCHITECTS, INC. "COPYRIGHT" YEAR OF FIRST PUBLICATION 2018 JORDAN ARCHITECTS, INC.

OB NUMBER: 17-606

CALE: 1"=30'

ATE: 06/19/2020






#### **KEY NOTES**

- 1 STANDING SEAM METAL ROOF.
- 2 DOWNSPOUT
- 3 GUTTE
- 4 TPO ROOFING SYSTEM.
- ROOF DRAIN & OVERFLOW.
- 6 ROOF ACCESS HATCH.
- 7 ELEVATOR PENTHOUSE.
- 8 TYPICAL PARAPET.

#### **GENERAL NOTES**

1. COPPER METAL ROOFING, COPPER GRANULE CONTAINING ASPHALT SHINGLES, COPPER GUTTERS AND DOWNSPOUTS, AND / OR OTHER EXTERIOR ORNAMENTAL COPPER ARE NOT PERMITTED FOR USE ON ANY COMMERCIAL OR INDUSTRIAL BUILDING.



# BAY AREA SELF STORAGE


CUPERTINO, CA


ROOF PLAN

THIS DRAWING AND ITS CONTENTS ARE INSTRUMENTS OF SERVICE AND ARE THE COPYRIGHTED PROPERTY OF JORDAN ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE PROJECT NOTED ABOVE AND MAY NOT BE REUSED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF JORDAN ARCHITECTS, INC. "COPYRIGHT" YEAR OF FIRST PUBLICATION 2018 JORDAN ARCHITECTS, INC.

-606 /=30' //2021







#### **BIKE & VEHICLE PARKING EXCEPTION**


**BIKE & VEHICLE PARKING EXCEPTION** 166,845 / 450 = 371 TOTAL VEHICLE PARKING SPACES ALLOWED PARKING SPACES = 41 41 SPACES / 371 SPACES = 9.0% OF TOTAL SPACES 166,185 / 12,000 = 14 TOTAL BIKE PARKING SPACES 14 X 9.9% = 2 TOTAL BIKE PARKING SPACES

#### BIKE LOCKER





# **KEY PLAN**

# BAY AREA SELF STORAGE




RESIDENCE FLOOR PLAN - 2ND FLOOR






BAY AREA SELF STORAGE

RESIDENCE FLOOR PLAN




3 NUMBER: 17-606 ALE: 1/4"=1'-0" E: 01/25/2021






### BUILDING A - SOUTH ELEVATION 1



#### **BUILDING A - EAST ELEVATION**



**BUILDING A - NORTH ELEVATION** 

# BAY AREA SELF STORAGE

CUPERTINO, CA

# ELEVATIONS

THIS DRAWING AND ITS CONTENTS ARE INSTRUMENTS OF SERVICE AND ARE THE COPYRIGHTED PROPERTY OF JORDAN ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE PROJECT NOTED ABOVE AND MAY NOT BE REUSED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF JORDAN ARCHITECTS, INC. "COPYRIGHT" YEAR OF FIRST PUBLICATION 2018 JORDAN ARCHITECTS, INC.

JOB NUMBER:

SCALE:

1/1

DATE:

0



OFFICE & RESIDENCE

METEOR DR.

**KEYNOTES** 

2 | HORIZONTAL & VERTICAL STUCCO REVEAL. 14 | PREFINISHED METAL GUTTER

**COLOR & MATERIAL BOARD** 

ORCO BLOCK. 8x8x16 SHOT BLAST COLOR:"BLACK 250", WEIGHT: MEDIUM

C2 COLOR TO MATCH MBCI SIGNATURE 300 COLOR: SLATE GRAY

C3 LA HABRA STUCCO FINISH FINISH: SAND FLOAT 20/30

C4 LA HABRA STUCCO FINISH FINISH: SAND FLOAT 20/30 COLOR: P-2090 THUNDER SKY

⟨C5⟩ STOREFRONT GLASS B - CLEAR

ARCHITECTURAL METAL PANEL: MBCI

G6 JANUS INTERNATIONAL COLOR: DARK TEAL

COLOR: "LIGHT STONE"

**KEY PLAN** 

⟨C7⟩ FINISH: SMOOTH

COLOR: X-16 SILVER GREY

1 STUCCO FINISH.

4 METAL AWNING.

7 ROLL-UP DOORS.

3 INTEGRAL CMU BLOCK.

FAUX ROLL-UP DOORS FOR DISPLAY

6 ARCHITECTURAL METAL FLUSH PANEL

10 STOREFRONT GLAZING WITH VISION GLASS

SIGNAGE UNDER SEPARATE PERMIT

SWING DOOR, PAINTED TO MATCH COLOR C6.

SIGNS TO COMPLY WITH CITY STANDARDS.

TELESCOPIC ALUMINUM ENTRY GLASS DOOR.

9 ELEVATOR PENTHOUSE

13 STUCCO FINISH BAND.

15 ROOF LINE BEHIND.

17 PARAPET BEYOND.

METAL ROOF.

19 PARAPET.


16 PREFINISHED METAL DOWNSPOUT

PREFINISHED STANDING SEAM

20 PREFINISHED METAL FLASHING


DAYLIGHT 12" O.C. ABOVE F.F. PROVIDE BRONZE NOZZLE.

23 ROOF MOUNTED FAN, SCREENED




BUILDING B - EAST ELEVATION (2)

BUILDING B - WEST ELEVATION (3)



**BUILDING B - SOUTH ELEVATION** 






# BAY AREA SELF STORAGE

CUPERTINO, CA


ELEVATIONS


THIS DRAWING AND ITS CONTENTS ARE INSTRUMENTS OF SERVICE AND ARE THE COPYRIGHTED PROPERTY OF JORDAN ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE PROJECT NOTED ABOVE AND MAY NOT BE REUSED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF JORDAN ARCHITECTS, INC. "COPYRIGHT" YEAR OF FIRST PUBLICATION 2018 JORDAN ARCHITECTS, INC.






#### BUILDING C - EAST ELEVATION (






BUILDING C - SOUTH ELEVATION (2)

BUILDING C - NORTH ELEVATION



BUILDING B - WEST ELEVATION 4





# BAY AREA SELF STORAGE

CUPERTINO, CA



REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN







# BAY AREA SELF STORAGE


SERVICE AND ARE THE COPYRIGHTED PROPERTY OF JORDAN ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE PROJECT NOTED ABOVE AND MAY NOT BE REUSED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN YEAR OF FIRST PUBLICATION 2018 JORDAN ARCHITECTS. INC.

ELEVATIONS









# TRASH ENCLOSURE - PLAN 1/4" = 1'-0" 7

TRASH ENCLOSURE 6


TRASH ENCLOSURE 5


KEY PAD SECTION


3/8" = 1'-0"

4

TYPICAL PERIMETER FENCE









8" CMU WALL

6" HIGH CONCRETE CURB

ADJACENT SURFACE

**GATE PANEL** 


8" CMU WALL


**GATE PANEL** 

GATE POST & HINDGE

6"x 6" TS GATE POST

STL. HINGES (SEE NOTE ABOVE)





CONCRETE FOUNDATION



- 6" ABOVE GRADE MIN

FRONT VIEW

PEDESTRIAN GATE

CONCRETE PAD

LEVEL W/TOP OF CURB

CONCRETE FOUNDATION

BUILDING

EXTERIOR WALL

4" SQUARE METAL TUBE

POST (SEE ELEVATIONS)

2 3/8" ROUND METAL

4" SQUARE METAL TUBE POST TO

STRUCTURAL FOR FOUNDATION. 4

HINGES MIN.

WELD METAL FENCE OR GATE. SEE


TUBING. TYP.

THIS DRAWING AND ITS CONTENTS ARE INSTRUMENTS OF ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN YEAR OF FIRST PUBLICATION 2018 JORDAN ARCHITECTS. INC




CUPERTINO, CA





## BUILDING A - PARTIAL SECTION LOOKING NORTH 1



BUILDING A - PARTIAL SECTION LOOKING NORTH 2

# KEYNOTES 1 CONC SLAB ON GRADE. 2 8" CMU EXTERIOR WALL. 3 STEEL-FRAMED EXTERIOR WALL WITH STUCCO FINISH. SEE ELEVATIONS. 4 CONC. FOOTING 5 ELEVATOR PENTHOUSE BEYOND 6 ROOFING SYSTEM 7 METAL FRAMED INTERIOR WALLS 8 ROLL-UP DOOR 9 CONC. OVER METAL DECK 10 CMU PIER BEYOND 11 NOT USED 12 PAVEMENT, SEE CIVIL. 13 PARAPET BEYOND. SEE ELEVATIONS. 14 FAN UNIT. SEE ELEVATIONS. **KEY PLAN**

# BAY AREA SELF STORAGE


CUPERTINO, CA


BUILDING SECTION


THIS DRAWING AND ITS CONTENTS ARE INSTRUMENTS OF SERVICE AND ARE THE COPYRIGHTED PROPERTY OF JORDAN ARCHITECTS, INC. THE USE IS EXPRESSLY INTENDED FOR THE PROJECT NOTED ABOVE AND MAY NOT BE REUSED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF JORDAN ARCHITECTS, INC. "COPYRIGHT" YEAR OF FIRST PUBLICATION 2018 JORDAN ARCHITECTS, INC.


JOB NUMBER: 17-606 SCALE: AS NOTED DATE: 01/25/202











CUPERTINO

APPROVED BY:

DRAWING NO.:

617010

RONALD EDMUND SANZO III R.C.E. NO. 79305, EXPIRES 3-31-22

636 Ninth Street | Oakland, CA 94607 | P. 510.873.8866 | www.sandis.net


SILICON VALLEY TRI-VALLEY CENTRAL VALLEY EAST BAY/SF

File: X:  $\P 617010(4)$  ENGINEERING(2) PLAN SETS(3) SHEET SETC2.1.dwg Date: Nov 11, 2020 - 3:30 PM

of 5 SHEET

ENLARGEMENT PLANS

CALIFORNIA




#### **GENERAL NOTES**

- 1. MINIMUM PLANT SIZES:
- STREET TREES (24"BOX), SITE TREES (15 GAL.), SHRUBS (1 GAL.), GROUNDCOVER (FLATS)

  2. IRRIGATION SYSTEM TO BE INSTALLED AS A PART OF SITE CONSTRUCTION. SYSTEM SHALL BE UNDERGROUND, AUTOMATIC WITH POP-UP SPRAY HEADS, "SMART" CONTROLLER AND AUTOMATIC RAIN SHUTOFF. LOW PRECIPITATION RATE HEADS TO BE USED TO MINIMIZE RUNOFF.
- 3. POINT OF CONNECTION FOR WATER SUPPLY, SHALL BE BY A NEW LANDSCAPE SUB METER.
- 4. ALL PLANTING AREAS SHALL RECEIVE A 3" LAYER OF MEDIUM BARK MULCH AFTER INSTALLATION.
- 5. ALL PLANT MATERIAL SHALL CONFORM TO THE CITY OF CUPERTINO OR STATE OF CALIFORNIA MODEL WATER CONSERVATION ORDINANCE.
- 6. ALL PLANTING AND IRRIGATION SHALL BE INSTALLED PER THE CITY OF CUPERTINO STANDARDS AND CODES.
- 7. FOR SITE WORK, ARCHITECTURAL, AND GRADING/DRAINAGE INFORMATION SEE PLANS BY OTHERS.
- 8. ALL AREAS BEYOND THE AREA OF WORK THAT ARE DISTURBED BY CONSTRUCTION SHALL BE RETURNED TO ORIGINAL CONDITION.
- 9. DRAWINGS ARE FOR DESIGN AND REVIEW PURPOSES ONLY AND SHALL NOT BE USED AS CONSTRUCTION
- TREES PLANTED IN AN AREA LESS THAN 8' WIDE SHALL BE INSTALLED WITH A ROOT BARRIER TO PROTECT AGAINST HARDSCAPE DAMAGE.
- 11. STREET TREES ARE TO BE SELECTED FROM THE CITY OF CUPERTINO APPROVED TREE LIST.

☐ CONCEPTUAL LANDSCAPE PLAN - C



**SCALE**: 1" = 20'-0"

NORTH

PLEINAIRE DESIGN GROUP

3203 Lightning St., Ste. 201 // Santa Maria, CA 93455 805.349.9695 // www.pleinairedg.com

THE DRAWING, DESIGN IDEAS, AND FEATURES OF CONSTRUCTION, DEPICTED WITHIN THE DRAWINGS ARE THE EXCLUSIVE PROPERTY OF KEVIN J. SMALL LANDSCAPE ARCHITECT. THEY ARE NOT TO BE REUSED, REPRODUCED, COPIED, SOLD, OR USED FOR ANY OTHER PURPOSE WITHOUT THE EXPRESSED WRITTEN CONSENT OF KEVIN J. SMALL; RLA 2929. @ 2018 KEVIN J. SMALL

OC-N-STOR

SHEET TITLE

# CONCEPTUAL LANDSCAPE PLAN A,B, & C

 OWNER
 Bass Cupertino, LLC

 10121 Miller Avenue, #200


 Cupertino, California 95014

 T: 408.255.4100

 DATE
 2018.03.05


SHEET NO.

CLP-01




☐ CONCEPTUAL LANDSCAPE PLAN - B

☐ CONCEPTUAL LANDSCAPE PLAN - C



SCALE: 1" = 20'-0"



**EXISTING PEDESTRIAN PATH** 

AND PUBLIC OPEN SPACE.

NO WORK TO OCCUR

**SCALE**: 1" = 20'-0"

PLEINAIRE DESIGN GROUP

3203 Lightning St., Ste. 201 // Santa Maria, CA 93455

805.349.9695 // www.pleinairedg.com

THE DRAWING, DESIGN IDEAS, AND FEATURES OF CONSTRUCTION, DEPICTED WITHIN THE DRAWINGS ARE THE EXCLUSIVE PROPERTY OF KEVIN J. SMALL LANDSCAPE ARCHITECT. THEY ARE NOT TO BE REUSED, REPRODUCED, COPIED, SOLD, OR USED FOR ANY OTHER PURPOSE WITHOUT THE EXPRESSED WRITTEN CONSENT OF KEVIN J. SMALL; RLA 2929. © 2020 KEVIN J. SMALL

AREA SELF-STORAGE

Q

 $\Box$ 

SHEET TITLE

CONCEPTUAL LANDSCAPE PLAN A,B, & C

 OWNER
 Bass Cupertino, LLC

 10121 Miller Avenue, #200

 Cupertino, California 95014

 T: 408.255.4100


 DATE
 2020.11.13

 21809

SHEET NO.

Meteor Dr.

NORTH N.T.S. CLP-01



#### TREE PRESERVATION GUIDELINES

Tree Preservation and Protection Plan

In providing recommendations for tree preservation, we recognize that injury to trees as a result A supplemental irrigation program is recommended for the ? trees and should be of construction include mechanical injuries to trunks, roots and branches, and injury as a result of changes that occur in the growing environment.

To minimize these injuries, we recommend grading operations encroach no closer than six times the trunk diameter, (i.e. 30" diameter tree x 6=180" distance). At this distance, buttress/anchoring roots would be preserved and minimal injury to the functional root area would be anticipated. Should encroachment within the area become necessary, hand digging is mandatory.

#### **Barricades**

Prior to initiation of construction activity, temporary barricades should be installed around all trees in the construction area. Six-foot high, chain link fences are to be mounted on steel posts, driven 2 feet into the ground, at no more than 10-foot spacing. The fences shall enclose the entire area under the drip line of the trees or as close to the drip line area as practical. These barricades will be placed around individual trees and/or groups of trees as the existing environment dictates.

The temporary barricades will serve to protect trunks, roots and branches from mechanical injuries, will inhibit stockpiling of construction materials or debris within the sensitive 'drip line' areas and will prevent soil compaction from increased vehicular/pedestrian traffic. No storage of Mulch material, topsoil, vehicles or equipment shall be permitted within the tree enclosure area. The ground around the tree canopy shall not be altered. Designated areas beyond the drip lines of any trees should be provided for construction materials and onsite parking.

#### Root Pruning (if necessary)

During and upon completion of any trenching/grading operation within a Tree Protection Zone, clean pruning cuts of exposed, damaged or severed roots greater than one inch diameter should be accomplished under the supervision of a qualified Arborist to minimize root deterioration beyond the soil line within twenty-four (24) hours.

Pruning of the foliar canopies to include removal of deadwood is recommended and should be initiated prior to construction operations. Such pruning will provide any necessary construction clearance, will lessen the likelihood or potential for limb breakage, reduce 'windsail' effect and provide an environment suitable for healthy and vigorous growth.

accomplished at regular three to four-week intervals during the period of May 1st through October 31<sup>st</sup>. Irrigation is to be applied at or about the 'drip line' in an amount sufficient to supply approximately ten (10) gallons of water for each inch in trunk diameter.

Irrigation can be provided by means of a soil needle, 'soaker' or permeable hose. When using 'soaker' or permeable hoses, water is to be run at low pressure, avoiding runoff/puddling, allowing the needed moisture to penetrate the soil to feeder root depths.

#### Fertilization

A program of fertilization by means of deep root soil injection is recommended with applications in spring and summer for those trees to be impacted by construction. Fertilizer should include organic blends and components such as mycorrhizae and bio stimulants.

Such fertilization will serve to stimulate feeder root development, offset shock/stress as related to construction and/or environmental factors, encourage vigor, alleviate soil compaction and compensate for any encroachment of natural feeding root areas.

Inception of this fertilizing program is recommended prior to the initiation of construction activity.

Mulching with wood chips (maximum depth 3") within tree environments (outer foliar perimeter) will lessen moisture evaporation from soil, protect and encourage adventitious roots and minimize possible soil compaction.

Periodic inspections by the **Site Arborist** are recommended during construction activities, particularly as trees are impacted by trenching/grading operations.

Inspections at approximate four (4) week intervals would be sufficient to assess and monitor the effectiveness of the Tree Preservation Plan and to provide recommendations for any additional care or treatment.

All written material appearing herein constitutes original and unpublished work of the Arborist and may not be duplicated, used or disclosed without written consent of the Arborist.

We thank you for this opportunity to be of assistance in your tree preservation concems.

Should you have any questions, or if we may be of further assistance in these concerns, kindly

#### McCLENAHAN CONSULTING, LLC

contact our office at any time.

#### John H. McClenahan

ISA Board Certified Master Arborist, WE-1476B member, American Society of Consulting Arborists

Trees one through thirteen are located on the City of Cupertino neighboring property. Proposed site improvements will include two bioretention areas that will require removal of eight trees (17-23 and 29). Trees scheduled for removal are not protected by city ordinance due to species. Tree Protection Zones have been defined for each tree as six times the trunk diameter from the root flare. Tree protection fencing should be installed as close to the TPZ or dripline as feasible, (whichever distance is greater). Figure 2 indicates the trees protected by City of Cupertino ordinance. Although it is recommended that grading and excavation do not occur within the TPZ, the following recommendations will help protect trees to remain should grading or excavation occur within a TPZ.

- Any grading or excavation within TPZ must be accomplished by hand or air digging
- A qualified arborist must supervise any cutting of roots within TPZ
- A qualified arborist must provide mitigation for any root cutting in the TPZ Adoption of Tree Preservation Guidelines will enhance prognosis

17 Red ironbark	19.2"	One 36-inch box tree
18 Red ironbark	15.8, 12.6, 14.5, 14.2, 13.7, 12.2"	One 36-inch box tree
19 Eucalyptus	20.6"	One 36-inch box tree
20 Eucalyptus	16.5"	One 36-inch box tree
21 Eucalyptus	23.3"	One 36-inch box tree
22 Eucalyptus	17.5, 10.3, 9°	One 36-inch box tree
23 Chinese pistache	18.1*	One 36-inch box tree
29 Tree of heaven	8.9°	One 24-inch box tree
NAME OF TAXABLE PARTY OF TAXABLE PARTY OF TAXABLE PARTY.	(SSA F 2 200 )	THE REPORT OF THE PERSONNELS AND THE PERSONNELS AND THE

Figure 1: Proposed removals with mitigation

# TREE REPLACEMENT LEGEND

TREES			
SYMBOL	NAME	SIZE	QTY.
0	EXISTING TREE TO REMAIN		30
	T2 EXISTING TREE TO BE REMOVED		8
	PLATANUS X ACERFOLIA 'BLOODGOOD' BLOODGOOD LONDON PLANE	36" BOX	7
	PISTACHIA CHINENSIS CHINESE PISTACHE	24" BOX	1

#### STREET TREE

SYMBO	L NAME	SIZE	QTY.
	PISTACIA CHINENSIS CHINESE PISTACHE	24" BOX	1

FOR MORE INFORMATION SEE THE ATTACHED ARBORIST REPORT & CLP-01.

**VICINITY MAP** 

# 3203 Lightning St., Ste. 201 // Santa Maria, CA 93455 COPIED, SOLD, OR USED FOR ANY OTHER PURPOSE WITHOUT THE EXPRESSED WRITTEN CONSENT OF KEVIN J. SMALL; RLA 2929. @ 2020 KEVIN J. SMALL

DESIGN GROUP

805.349.9695 // www.pleinairedg.com



Meteor Dr.

**NORTH** 

#### **TREE REPLACEMENT PLAN**

OWNER	Bass Cupertino, LLC
	10121 Miller Avenue, #20
	Cupertino, California 9501
	T: 408.255.410
DATE	2020.11.1
	2180

SHEET NO.






Small Cape Rush



Bearberry Cotoneaster



Rock Purslane




Molate Red Fescue



Variegated Lily Turf



Creeping Myoporum



Gold Mound Lantana



Berkeley Sedge



Giant Chain Fern



3203 Lightning St., Ste. 201 // Santa Maria, CA 93455 805.349.9695 // www.pleinairedg.com

Natal Plum

THE DRAWING, DESIGN IDEAS, AND FEATURES OF CONSTRUCTION, DEPICTED WITHIN THE DRAWINGS ARE THE EXCLUSIVE PROPERTY OF KEVIN J. SMALL LANDSCAPE ARCHITECT. THEY ARE NOT TO BE REUSED, REPRODUCED, COPIED, SOLD, OR USED FOR ANY OTHER PURPOSE WITHOUT THE EXPRESSED WRITTEN CONSENT OF KEVIN J. SMALL; RLA 2929. @ 2018 KEVIN J. SMALL

S-N-STOR

SHEET TITLE

#### PLANT IMAGERY

 OWNER
 Bass Cupertino, LLC

 10121 Miller Avenue, #200

 Cupertino, California 95014

 T: 408.255.4100

 DATE
 2018.03.05

SHEET NO.

CLP-02

#### CITY OF CUPERTINO

#### WATER EFFICIENT LANDSCAPE WORKSHEET

City of Santa Mari	ia Reference I	Evapotranspira	ition (ETo):		45.3		
Hydrozone # /Planting Description a	Plant Factor (PF)	Irrigation Method b	Irrigation Effciency (IE)c	ETAF (PF/IE)	Landscape Area (sq, ft,)	ETAF x Area	Estimated Total Water Use (ETWU) e
Regular Landscape Ar	reas						
Very Low	0.1	drip	0.81	0.12	-	-	=
Low	0.2	drip	0.81	0.25	-	-	-
Low	0.3	drip	0.81	0.37	24,008.40	8,892.00	249,740.71
Medium	0.5	drip	0.81	0.62	1,263.60	780.00	21,907.08
Non-irrigated	0		0.81	0.00	-	-	-
				Totals	25,272.00	9,672.00	271,647.79
Special Landscape Are	eas	•					
Turf				1	-	-	-
						-	-
						-	-
						-	-
				24444444444444444444		-	-
				Totals	-	-	D.
						ETWU Total	271,647.79
Maximum Allowed W	/ater Allowance	(MAWA)e					319,405.23
E.g 1.) fro	#/Planting Des	·		b Irrigation M overhead or drip		<b>c Irrigation Eff</b> 0.75 for spr 0.81 for dr	ray head

#### d ETWU (Annual Gallons Required)

= Eto x 0.62 x ETAF x Area
where 0.62 is a conversion factor
that converts acre-inches per acre
per year to gallons per square foot

2.) medium water use planting

#### MAWA (Annual Gallons Allowed)

= (Eto) ( 0.62) [ (ETAF x LA) + ((1-ETAF) x SLA)] where 0.62 is a conversion factor that converts acre- inches per acre per year to gallons per square foot per year, LA is the total landscape area in square feet, SLA is the total special landscape area in square feet, and ETAF is .55 for residential areas and 0.45 for non-residential areas.

#### **ETAF Calculations:**Average ETAF for Regular Landscape Areas must be 0.55 or below for residential areas, and 0.45 or below for non-residential areas.

Total ETAF x Area (B+D)	9,672
Total Area (A+C)	25,272
Sitewide ETAF (B+D) ÷ (A+C)	

Regular	
Total ETAF x Area (B)	9,672.00
Total Area (A)	25,272.00
Average ETAF (B÷A)	0.38

#### NOTE:

PLANT IMAGERY SHOWN IS REPRESENTATIVE ONLY. FINAL SELECTIONS MAY VARY. SEE CONCEPTUAL PLANTING LEGEND FOR MORE INFORMATION.

Lowboy Acacia



Small Cape Rush



Bearberry Cotoneaster



Santa Barbara Mexican Bush Sage



Molate Red Fescue



Variegated Lily Turf

PLANT IMAGERY SHOWN IS

REPRESENTATIVE ONLY. FINAL

SELECTIONS MAY VARY. SEE

FOR MORE INFORMATION.

CONCEPTUAL PLANTING LEGEND

NOTE:



Creeping Myoporum



Gold Mound Lantana

California Grey Rush



Berkeley Sedge

Bloodgood London Plane



Natal Plum



Karl Foerster Feather Reed Grass



Chinese Pistache

# LANDSCAPE AREA: 24,494 SQ. FT.

CITY OF CUPERTINO

NORTH

#### WATER EFFICIENT LANDSCAPE WORKSHEET

Project:		i Si		19 10			
Hydrozone # /Planting Description a	Plant Factor (PF)	Irrigation Method b	Irrigation Efficiency (IE)c	ETAF (PF/IE)	Landscape Area (sq, ft,)	ETAF x Aren	Estimated Total Water Use (ETWU) e
Regular Landscape An	eas			4	<u> </u>		
Very Low	0.1	drip	0.81	0.12	-1	15	5
Low	0.2	drip	0.81	0.25	-	57	
Low	0.3	drip	0.81	0.37	23,230.00	8,603.70	241,643.62
Medium	0.5	drip	0.81	0.62	1,264.00	780.25	21,914.01
Non-irrigated	0		0.81	0.00	-	<b>5</b>	**
	===	9		Totals	24,494.00	9,383.95	263,557.64
Special Landscape Are	95	578-	539 -	<u> </u>	\$ \$\$\$		
Turf				1	-	¥,	2.
						9	32
						18	±
						55 T	55
					3		=
				Totals	3	-	200
						ETWU Total	263,557.64
Maximum Allowed W	ster Alleman en	MANUAL -					309,572.32

Hydrozone #/Planting Description

1.) front lawn 2.) medium water use planting

ETWU (Annual Gallons Required) = Eto x 0.62 x ETAF x Area where 0.62 is a conversion factor that converts acre-inches per acre per year to gallons per square foot per year.

MAWA (Annual Gallons Allowed)

Irrigation Method

overhead spray

or drip

= (Eto) ( 0.62) [ (ETAF x LA) + ((1-ETAF) x SLA)] where 0.62 is a conversion factor that converts acre-inches per acre per year to gallons per square foot per year, LA is the total landscape area in square feet, SLA is the total special landscape area in square feet, and ETAF is .55 for residential areas and 0.45 for non-residential areas.

c Irrigation Efficiency

0.81 for drip

0.75 for spray head

ETAF Calculations: Average ETAF for Regular Landscape Areas must be 0.55 or below for residential areas, and 0.45 or below for nonresidential areas.

FxAres (B+D)	9,383.95
s (A+C)	24,494.00

Regular	
Total ETAF x Area (B)	9,383.95
Total Area [A]	24,494.00
Average ETAF (B + A)	0.3

# DESIGN GROUP

3203 Lightning St., Ste. 201 // Santa Maria, CA 93455 805.349.9695 // www.pleinairedg.com

SHEET TITLE

PLANT IMAGERY & AREA MAP

4

OWNER Bass Cupertino, LLC 10121 Miller Avenue, #200 Cupertino, California 95014 T: 408.255.4100 2020.11.13 DATE

SHEET NO.

CLP-03

21809